

Filter Fan



Description


Order Number:	4883A4103
Brand Name:	SOLIFLEX
Color:	RAL 9005
Housing Material:	ABS Plastic
Ingress protection:	IP 54, Type 12
Note:	Umgekehrter Luftstrom
Approvals:	CE, cURus, cULus
UL File Number:	E498756

Technical data


Operating temperature range:	14°F - 131°F
Air volume flow unimpeded:	483 cfm / 547 cfm
Static pressure:	0.86 inH2O @ 50 Hz 0.88 inH2O @ 60 Hz
Dimension H x W x D:	12.8 x 12.8 x 6.3 inch
Weight:	9.37 lbs.
Cut out dimensions:	11.45 x 11.45 inch (+0.06)
Voltage / Frequency:	230 V ~ 50/60 Hz
Rated current:	0.55 A / 0.74 A
Power consumption:	125 / 166 W
Degree of separation:	85% - DIN 24185
Wall thickness:	0.06 - 0.10 in.
Filter class:	G3 according to EN 779
Installation:	Elastic clips or by 4 self-threading screws
Noise level:	66 dB(A) @ 50 Hz 69.2 dB(A) @ 60 Hz

Air flow:

Q = Air flow [cfm]
P = Static pressure [inH2O]



Cut out dimensions:



Order Information

Taric code	84145915
GTIN (EAN)	5350604100800