



## Description

<b>Order Number:</b>	87061584USL
<b>Brand Name:</b>	SOLITHERM PROTEC
<b>Color:</b>	RAL 7035
<b>Housing Material:</b>	Stainless steel AISI 316 (V4A)
<b>Ingress protection:</b>	IP 56 / Type 12, 3, 3R, 4, 4X
<b>Included:</b>	Metal mesh filter
<b>Approvals:</b>	CE, UL(ACVS), cULus

## Technical data


<b>Cooling capacity 95F/95F:</b>	2,149 BTU/hr @ 50 Hz 2,269 BTU/hr @ 60 Hz
<b>Cooling capacity 95F/122F:</b>	1,740 BTU/hr @ 50 Hz 1,808 BTU/hr @ 60 Hz
<b>Enclosure heater:</b>	150 W
<b>Compressor type:</b>	rotary piston compressor
<b>Refrigerant / GWP:</b>	R 134a / 1430
<b>Refrigerant charge:</b>	97 g / 3.4 oz
<b>High / low pressure:</b>	28 / 6 bar 406 / 88 psi
<b>Operating temperature range:</b>	-40°C - 60°C
<b>UL temperature range:</b>	-40°C - 55°C
<b>Air volume flow (system / unimpeded):</b>	Ambient: 235 / 408 m <sup>3</sup> /h Cabinet: 115 / 180 m <sup>3</sup> /h
<b>Mounting:</b>	Wall mounted
<b>Dimension H x W x D:</b>	15 x 9.85 x 9.85 inch
<b>Weight:</b>	15.7 kg
<b>Voltage / Frequency:</b>	120 V ~ 50/60 Hz
<b>UL Voltage / Frequency:</b>	120 V ~ 60 Hz
<b>Current 95F95F:</b>	4.9 A @ 50 Hz 3.9 A @ 60 Hz
<b>Starting current:</b>	13 A
<b>Max. current:</b>	5.1 A
<b>Nominal power 95F95F:</b>	420 W @ 50 Hz 435 W @ 60 Hz
<b>Max. power:</b>	570 W
<b>Fuse:</b>	15 A (T)
<b>Max circuit ampacity:</b>	15 A
<b>Short-circuit current rating:</b>	5 kA
<b>Rated current compressor:</b>	3.7 A

---


<b>Full load current fans:</b>	0.38 A
<b>Connection:</b>	5 pole terminal block for signals 4 pole terminal block for power 3 pole terminal block for RS 485 MODBUS

---

**Performance graph:**



**Cut out dimensions:**



## Order Information

<b>Box dimensions</b>	87061184
<b>Gross weight</b>	87061484
<b>Taric Code</b>	84158200