

Enclosure air conditioner, 5100 BTU



Description

| | |
|----------------------------|--------------------------------|
| Order Number: | 87152082USL |
| Brand Name: | SOLITHERM PROGRESSIVE |
| Housing Material: | Stainless steel AISI 304 (V2A) |
| Ingress protection: | IP 56 / Type 12, 3, 3R, 4, 4X |
| Included: | With metal mesh filter |
| Approvals: | CE, UL(ACVS), cULus |
| UL File Number: | SA32278 |

Technical data

| | |
|--|--|
| Cooling capacity 95F/95F: | 5120 BTU @ 60 Hz |
| Cooling capacity 95F/122F: | 3650 BTU @ 50 Hz 3820 BTU @ 60 Hz |
| EER 95F95F: | 6.7 / 6.1 |
| Compressor type: | Reciprocating compressor |
| Refrigerant / GWP: | R 134a / 1430 |
| Refrigerant charge: | 275 g / 9.7 oz |
| High / low pressure: | 435 / 87 psig |
| Operating temperature range: | -40°F - 140°F |
| Air volume flow (system / unimpeded): | Ambient: 330 / 520 cfm Enclosure: 360 / 520 cfm |
| Mounting: | Wall mounted |
| Dimension H x W x D: | 35 x 15.6 x 12 inch |
| Weight: | 89 lbs. |
| Voltage / Frequency: | 400/460 V - 50/60 Hz 2~ |
| UL Voltage / Frequency: | 460 V / 60Hz 2~ |
| Current 95F95F: | 1.7 A @ 50 Hz 1.85 A @ 60 Hz |
| Starting current: | 12 A |
| Max. current: | 2.4 A |
| Nominal power 95F95F: | 740 W @ 50 Hz 855 W @ 60 Hz |
| Max. power: | 1.08 kW |
| Fuse: | 15 A (T) |
| Max circuit ampacity: | 15 A |
| Short-circuit current rating: | 5 kA |
| Rated current compressor: | 1.4 A |
| Full load current fans: | 0.4 A |


Connection:

5 pole terminal block for signals

4 pole terminal block for power

3 pole terminal block for RS 485 MODBUS

Performance graph:



Cut out dimensions:

