

## Enclosure air conditioner 9500 BTU



### Description

<b>Order Number:</b>	873005201USL
<b>Brand Name:</b>	SOLITHERM PROGRESSIVE
<b>Color:</b>	RAL 7035
<b>Housing Material:</b>	Mild steel, powder coated
<b>Ingress protection to EN 60 529:</b>	IP 56 / Type 12, 3, 3R, 4
<b>Approvals:</b>	CE, UL(ACVS), cULus
<b>UL File Number:</b>	SA32278

## Technical data

<b>Cooling capacity 95F/95F:</b>	9500 BTU
<b>Cooling capacity 95F/122F:</b>	7675 BTU @ 50 Hz 8020 BTU @ 60 Hz
<b>Enclosure heater:</b>	1,000 W
<b>Compressor type:</b>	Reciprocating compressor
<b>Refrigerant / GWP:</b>	R 513A / 630
<b>Refrigerant charge:</b>	360 g / 12.7 oz
<b>High / low pressure:</b>	30 / 6 bar 435 / 88 psi
<b>Air volume flow (system / unimpeded):</b>	Ambient: 440 / 520 cfm Enclosure: 440 / 520 cfm
<b>Operating temperature range:</b>	-40°F - 140°F
<b>UL temperature range:</b>	-40°F - 140°F
<b>Mounting:</b>	Wall mounted
<b>Dimension H x W x D:</b>	35 x 15.6 x 12 inch
<b>Weight:</b>	50 kg
<b>Voltage / Frequency:</b>	230 V ~ 50/60 Hz
<b>UL Voltage / Frequency:</b>	230 V ~ 60 Hz
<b>Current 95F95F:</b>	5.4 A @ 50 Hz 7.0 A @ 60 Hz
<b>Starting current:</b>	22.5 A
<b>Max. current:</b>	8.7 A
<b>Nominal power 95F95F:</b>	1.22 kW @ 50 Hz 1.57 kW @ 60 Hz
<b>Max. power:</b>	2.0 kW
<b>Fuse:</b>	15 A (T)
<b>Max circuit ampacity:</b>	15 A
<b>Short-circuit current rating:</b>	5 kA
<b>Rated current compressor:</b>	5 A
<b>Full load current fans:</b>	0.73 A

**Connection:**

5 pole terminal block for signals

4 pole terminal block for power

3 pole terminal block for RS485

---

**Performance graph:**

