

## Thermoelectric cooler TG 3050-24V External




### Description

<b>Brand Name:</b>	SoliTherm Peltier
<b>Order Number:</b>	3050305
<b>Housing Material:</b>	Stainless steel AISI 304 (V2A)
<b>Ingress protection:</b>	IP 66, NEMA / UL Type 4X
<b>Note:</b>	The torque for the mounting nuts should be 4.5 Nm.
<b>Approvals:</b>	CE, cURus


## Technical data TG 3050-24V External

<b>Cooling capacity 95F/95F:</b>	170 BTU
<b>Operating temperature range:</b>	-4°F - 149°F
<b>Air volume flow (system / unimpeded):</b>	Ambient air circuit: 37 / 100 cfm Cabinet air circuit: 13 / 42 cfm
<b>Mounting:</b>	External (with frame)
<b>Dimension H x W x D:</b>	11.9 x 6.2 x 5.4 inch
<b>Weight:</b>	9 lbs.
<b>Cut out dimensions:</b>	10.63 x 5.12 inch
<b>Voltage / Frequency:</b>	24 V DC (use NEC Class 2 supply)
<b>Current 95F95F:</b>	2.4 A
<b>Starting current:</b>	3.7 A
<b>Max. current:</b>	2.5 A
<b>Nominal power 95F95F:</b>	57.6 W
<b>Max. power:</b>	60 W
<b>Fuse:</b>	4 A (T)
<b>Connection:</b>	Connection terminal block


**Performance Graph:**



**Air flow:**



**Cut out dimensions:**



## Bestellinformationen

<b>Stainless steel AISI 316 (V4A) housing part no.</b>	30503054
<b>Verpackungsmaße</b>	244 x 142 x 159 mm
<b>Bruttogewicht</b>	4.6 kg
<b>Taric code</b>	84158300
<b>GTIN (EAN)</b>	5350604350007