

Thermoelectric cooler TG 3102-24V External




Description

Brand Name:	SoliTherm Peltier
Order Number:	3102305
Housing Material:	Stainless steel AISI 304 (V2A)
Ingress protection:	IP 66, NEMA / UL Type 4X
Note:	The torque for the mounting nuts should be 4.5 Nm.
Approvals:	CE, cURus


Technical data TG 3102-24V External

Cooling capacity 95F/95F:	340 BTU
Operating temperature range:	-4°F - 149°F
Air volume flow (system / unimpeded):	Ambient air circuit: 75 / 125 cfm Cabinet air circuit: 27 / 53 cfm
Mounting:	External (with frame)
Dimension H x W x D:	11.9 x 12 x 5.5 inch
Weight:	16 lbs.
Cut out dimensions:	10.63 x 10.63 in.
Voltage / Frequency:	24 V DC
Current 95F95F:	4.8 A
Starting current:	7.4 A
Max. current:	4.9 A
Nominal power 95F95F:	115 W
Max. power:	118 W
Fuse:	8 A (T)
Connection:	Connection terminal block


Performance Graph:



Air flow:



Cut out dimensions:



Bestellinformationen

Stainless steel AISI 316 (V4A) housing part no.	31023054
Verpackungsmaße	235 x 380 x 190.5 mm
Bruttogewicht	9 kg
Taric code	84158300
GTIN (EAN)	5350604350144