

Thermoelectric cooler TG 3152-24V External




Description

Order Number:	3152305
Housing Material:	Stainless steel AISI 304 (V2A)
Ingress protection:	IP 66, NEMA / UL Type 4X
Note:	The torque for the mounting nuts should be 4.5 Nm.
Approvals:	CE, cURus


Technical data TG 3152-24V External

Cooling capacity 95F/95F:	510 BTU
Operating temperature range:	-4°F - 149°F
Air volume flow (system / unimpeded):	Ambient air circuit: 70 / 153 cfm Cabinet air circuit: 35 / 100 cfm
Mounting:	External (with frame)
Dimension H x W x D:	19.7 x 7.4 x 6.9 inch
Weight:	28 lbs.
Cut out dimensions:	18.4 x 6.1 inch
Voltage / Frequency:	24 V DC
Current 95F95F:	7 A
Starting current:	11 A
Max. current:	7.5 A
Nominal power 95F95F:	170 W
Max. power:	180 W
Fuse:	10 A (T)
Connection:	Connection terminal block


Performance Graph:



Air flow:



Cut out dimensions:



Bestellinformationen

Stainless steel AISI 316 (V4A) housing part no.	31523054
Verpackungsmaße	486.6 x 205 x 183.5 mm
Bruttogewicht	14.7 kg
Taric code	84158300
GTIN (EAN)	5350604350250