

Enclosure air conditioner KG 4315-120V Recessed




Description

Brand Name:	SoliTherm ComPact
Order Number:	43151081
Color:	RAL 7035
Housing Material:	Mild steel, powder coated
Ingress protection:	Type 12
Approvals:	CE, cURus, cULus


Technical data KG 4315-120V Recessed

Cooling capacity 95F/95F:	5,560 BTU
Cooling capacity 95F/122F:	4,500 BTU
Compressor:	Reciprocating compressor
Refrigerant / GWP:	R134a / 1430
Refrigerant charge:	420 g / 14.8 oz
High / low pressure:	25.5 / 6 bar 370 / 88 psig
Operating temperature range:	50°F - 131°F
Air volume flow (system / unimpeded):	Ambient air circuit: 280 / 500 cfm Cabinet air circuit: 225 / 324 cfm
Mounting:	Recessed
Dimension H x W x D:	41 x 17.8 x 10.6 inch
Weight:	105 lbs.
Cut out dimensions:	15.5 x 36.8 inch
Voltage / Frequency:	120 V ~ 60 Hz
Current 95F95F:	9.6 A
Starting current:	39.4 A
Max. current:	11.8 A
Nominal power 95F95F:	880 W
Max. power:	1.29 kW
Fuse:	16 A (T)
Connection:	Connection terminal block


Performance Graph:



Air flow:



Cut out dimensions:



Bestellinformationen

Stainless steel housing part no.	43151026
Taric code	84158200
GTIN (EAN)	5350604360730