

Enclosure air conditioner KG 4330-230V




Description

Brand Name:	SoliTherm ComPact
Order Number:	43300001
Color:	RAL 7035
Housing Material:	Mild steel, powder coated
Ingress protection:	Type 12
Approvals:	CE, cURus, cULus


Technical data KG 4330-230V

Cooling capacity 95F/95F:	10240 BTU
Cooling capacity 95F/122F:	8560 BTU
Compressor:	Rotary piston compressor
Refrigerant / GWP:	R134a / 1430
Refrigerant charge:	900 g / 31.7 oz
High / low pressure:	29.5 / 6 bar 425 / 88 psig
Operating temperature range:	50°F - 131°F
Air volume flow (system / unimpeded):	Ambient air circuit: 441 / 706 cfm Cabinet air circuit: 506 / 706 cfm
Mounting:	External
Dimension H x W x D:	48.4 x 19.7 x 13.4 inch
Weight:	149 lbs.
Cut out dimensions:	44.48 x 16.92 inch
Voltage / Frequency:	230 V ~ 50/60 Hz
Current 95F95F:	5.6 A @ 50 Hz 7.6 A @ 60 Hz
Starting current:	25.1 A
Max. current:	9.2 A
Nominal power 95F95F:	1,33 kW @ 50 Hz 1,69 kW @ 60 Hz
Max. power:	1,61 kW @ 50 Hz 2,06 kW @ 60 Hz
Fuse:	16 A (T)
Connection:	Connection terminal block


Performance Graph:



Air flow:



Cut out dimensions:



Bestellinformationen

Stainless steel housing part no.	4330002
Mit Kondensatverdunstung Bestell Nr.	43300101
Verpackungsmaße	1,265 x 543 x 375 mm
Bruttogewicht	71.5 kg
Taric code	84158200
GTIN (EAN)	5350604361041