

## Filter Fan FL 4620A 230V



### Description


<b>Order Number:</b>	4620A4000
<b>Color:</b>	RAL 7035
<b>Housing Material:</b>	ABS Plastic
<b>Ingress protection:</b>	NEMA 12
<b>Optional:</b>	# 4620A4003 black # 4620A4033 black, NEMA 3R
<b>Approvals:</b>	CE, cULus, CSA
<b>Taric Code:</b>	84145915

## Technical data FL 4620A 230V

<b>Operating temperature range:</b>	14°F - +131°F
<b>Static pressure:</b>	0.46 inH2O @ 50Hz 0.62 inH2O @ 60Hz
<b>Dimension H x W x D:</b>	9.8 x 9.8 x 4.9 inch
<b>Weight:</b>	3.3 lbs
<b>Cut out dimensions:</b>	8.8 x 8.8 (+0.06) inch
<b>Voltage / Frequency:</b>	230 V ~ 50/60 Hz
<b>Rated current:</b>	0.134 A / 0.16 A
<b>Power consumption:</b>	32 W / 36 W
<b>Degree of separation:</b>	85% - DIN 24185
<b>Wall thickness:</b>	0.06 - 0.10 in.
<b>Filter class:</b>	G3 according to EN 779
<b>Installation:</b>	Elastic clips or by 4 self-threading screws
<b>Noise level:</b>	50 dB(A) @ 50 Hz 55 dB(A) @ 60 Hz

**Air flow:**

Q = Air flow [m<sup>3</sup>/h]  
 P = Static pressure [Pa]



**Cut out dimensions:**

