

Filter Fan FL 4830A 230V-R



Description


Order Number:	4830A4100
Color:	RAL 7035
Housing Material:	ABS Plastic
Ingress protection:	NEMA 12
Note:	Umgekehrter Luftstrom
Optional:	Different housing colours available on request With NEMA 3R protection part no. 4830A4130
Approvals:	CE, cULus, CSA
Taric Code:	84145915

Technical data FL 4830A 230V-R

Operating temperature range:	14°F - +131°F
Static pressure:	0.72 inH2O @ 50Hz / 0.78 inH2O @ 60Hz
Dimension H x W x D:	12.8 x 12.8 x 6.3 inch
Weight:	6.8 lbs
Cut out dimensions:	11.5 x 11.5 (+0.06) inch
Voltage / Frequency:	230 V ~ 50/60 Hz
Rated current:	0.31 A / 0.35 A
Power consumption:	70 W / 85 W
Degree of separation:	85% - DIN 24185
Wall thickness:	0.06 - 0.10 in.
Filter class:	G3 according to EN 779
Installation:	Elastic clips or by 4 self-threading screws
Noise level:	65.3 dB(A) @ 50 Hz 68.1 dB(A) @ 60 Hz

Air flow:

Q = Air flow [m³/h]
 P = Static pressure [Pa]



Cut out dimensions:

