

Filter Fan FL 4883A 400V



Description

| | |
|----------------------------|-------------|
| Order Number: | 4883A9000 |
| Color: | RAL 7035 |
| Housing Material: | ABS Plastic |
| Ingress protection: | NEMA 12 |
| Approvals: | CE, cULus |
| UL File Nummer: | E498756 |
| Taric Code: | 84145915 |

Technical data FL 4883A 400V

Operating temperature range: 14°F - 131°F

Dimension H x W x D: 12.8 x 12.8 x 6.3 inch

Weight: 9.37 lbs.

Cut out dimensions: 11.45 x 11.45 inch (+0.06)

Voltage / Frequency: 400/460 V ~ 50/60 Hz

Rated current: 0.20 A / 0.24 A

Power consumption: 110 W / 145 W

Wall thickness: 0.06 - 0.10 inch

Filter class: G3 according to EN 779

Elastic clips or by 4 self-threading screws.

Installation:

This device is to be installed in a Listed, appropriately UL Environmentally Type Rated Industrial Control Panel.
The device can be installed with or without vent filter according to UL508A and Environmental requirements.

Noise level: 66 dB(A) @ 50 Hz
69.2 dB(A) @ 60 Hz

Air flow:

Q = Air flow [cfm]
P = Static pressure [inH2O]



Cut out dimensions:

