

## Enclosure air conditioner



## Description

|                            |                           |
|----------------------------|---------------------------|
| <b>Order Number:</b>       | 43250001                  |
| <b>Brand Name:</b>         | COMPACT INDOOR            |
| <b>Color:</b>              | RAL 7035                  |
| <b>Housing Material:</b>   | Mild steel, powder coated |
| <b>Ingress protection:</b> | TYPE 12                   |
| <b>Approvals:</b>          | CE, cURus, cULus          |

## Technical data

|  |  |
|--|--|
| <b>Cooling capacity 95F/95F:</b>             | 8560 BTU   |
| <b>Cooling capacity 95F/122F:</b>            | 7160 BTU   |
| <b>Compressor type:</b>                      | Rotary piston compressor   |
| <b>Refrigerant / GWP:</b>                    | R134a / 1430   |
| <b>Refrigerant charge:</b>                   | 850 g / 30 oz  |
| <b>High / low pressure:</b>                  | 29.5 / 6 bar<br>425 / 88 psig  |
| <b>Operating temperature range:</b>          | 50°F - 131°F   |
| <b>Air volume flow (system / unimpeded):</b> | Ambient air circuit: 441 / 706 cfm<br>Cabinet air circuit: 323 / 706 cfm |
| <b>Mounting:</b>                             | External   |
| <b>Dimension H x W x D:</b>                  | 48.4 x 19.7 x 13.4 inch  |
| <b>Weight:</b>                               | 143 lbs.   |
| <b>Cut out dimensions:</b>                   | 44.48 x 16.92 inch   |
| <b>Voltage / Frequency:</b>                  | 230 V ~ 50/60 Hz   |
| <b>UL Voltage / Frequency:</b>               | 230 V ~ 60 Hz  |
| <b>Current 95F95F:</b>                       | 3.9 A @ 50 Hz<br>5.3 A @ 60 Hz   |
| <b>Starting current:</b>                     | 23 A   |
| <b>Max. current:</b>                         | 6.6 A  |
| <b>Nominal power 95F95F:</b>                 | 910 W @ 50 Hz<br>1.16 kW @ 60 Hz   |
| <b>Max. power:</b>                           | 1.19 kW @ 50 Hz<br>1.48 kW @ 60 Hz                                       |
| <b>Fuse:</b>                                 | 10 A (T)   |
| <b>Short-circuit current rating:</b>         | 5 kA   |
| <b>Connection:</b>                           | Connection terminal block  |



## Order Information

|   |                      |
|---|----------------------|
| <b>Stainless steel housing part no.</b>     | 4325002              |
| <b>Mit Kondensatverdunstung Bestell Nr.</b> | 43250101             |
| <b>Verpackungsmaße</b>                      | 1,265 x 543 x 375 mm |
| <b>Bruttogewicht</b>                        | 69 kg                |
| <b>Taric code</b>                           | 84158200             |