

Enclosure air conditioner 5100 BTU



Description

Order Number:	871500201USL
Brand Name:	SOLITHERM PROGRESSIVE
Housing Material:	Mild steel, powder coated
Ingress protection:	IP 56 / Type 12, 3, 3R, 4
Included:	Metal mesh filter
Approvals:	CE, UL(ACVS), cULus
UL File Number:	SA32278

Technical data

Cooling capacity 95F/95F:	5120 BTU
Cooling capacity 95F/122F:	3650 BTU @ 50 Hz 3820 BTU @ 60 Hz
EER 95F95F:	6.7 / 6.1
Compressor type:	Reciprocating compressor
Refrigerant / GWP:	R 134a / 1430
Refrigerant charge:	275 g / 9.7 oz
High / low pressure:	435 / 87 psig
Operating temperature range:	-40°F - 140°F
UL temperature range:	-40°F - 140°F
Air volume flow (system / unimpeded):	Ambient: 330 / 520 cfm Enclosure: 360 / 520 cfm
Mounting:	Wall mounted
Dimension H x W x D:	35 x 15.6 x 12 inch
Weight:	89 lbs.
Voltage / Frequency:	230 V ~ 50/60 Hz
UL Voltage / Frequency:	230 V ~ 60 Hz
Current 95F95F:	3.4 A @ 50 Hz 3.7 A @ 60 Hz
Starting current:	16 A
Max. current:	4.5 A
Nominal power 95F95F:	740 W @ 50 Hz 855 W @ 60 Hz
Max. power:	1.08 kW
Fuse:	15 A (T)
Max circuit ampacity:	15 A
Short-circuit current rating:	5 kA
Rated current compressor:	2.5 A
Full load current fans:	0.73 A


Connection:

5 pole terminal block for signals

4 pole terminal block for power

3 pole terminal block for RS 485 MODBUS

Performance graph:



Cut out dimensions:

